

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



(19)

(11) Publication number:

62235975 A

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **61078095**(51) Intl. Cl.: **G03G 15/04**(22) Application date: **07.04.86**

(30) Priority:

(43) Date of application
publication: **16.10.87**(84) Designated contracting
states:(71) Applicant: **CANON INC**(72) Inventor: **KIMIZUKA JUNICHI
INUYAMA SATOHIKO
SOYA TAKASHI**

(74) Representative:

**(54) LIGHT QUANTITY
CONTROL DEVICE**

(57) Abstract:

PURPOSE: To reduce an error at the control of the quantity of a laser beam by changing a laser current by one step and then comparing the quantity of detected light with the delay of a fixed time for converging a transient phenomenon.

CONSTITUTION: The quantity of a beam outputted from a laser 1 is detected by a detecting photodiode 8,

arithmetically amplified 13 and then A/D converted in a microprocessor MPU14, the digital signal is compared with a reference value selected out of plural reference values stored in a ROM14-2 in accordance with light quantity switching signals S1WS3 and a signal corresponding to the reference value is outputted from the MPU14. The output signal is D/A converted 15 and supplied to a constant current circuit 20 through a current/ voltage converting circuit 18 to control the driving current of the laser 1 through transistors 22, 25, 26, so that quantity of the laser beam is adjusted. If the values of output ports 01W09 of the MPU14 are changed by one bit, the current of the laser 1 is increased like steps, and after the passage of a waiting time for converging the transient variation of driving currents of the converter 15 and amplifiers 19, 21, the quantity of the laser beam is detected.

COPYRIGHT: (C)1987,JPO&Japio

